

MP24

Producer	Condor Carpets BV, Hasselt
Type	Tufted synthetic grass carpet
Material	Polyethylene (UV Stabilized)
Yarn type	8.800 / 1 dTex fibrillated straight
Yarn quality	Environmental friendly, free of lead and cadmium
Primary backing	100% PP Thiobac with fiber locked fleece, black, U.V. stabilized, weight 172 gr/m ²
Secondary backing	Black Latex compound with a base of sturenebutadiene (SBR), with drainage holes,836 gr/m ²
Water permeability	60 liter /min /100 cm ²
Pile height	24 mm +/- 10 %
Face weight	1.080 gr/m ² +/- 10 %
Total weight	2.088 gr/m ² +/- 10 %
Tuft gauge	3/8 gauge
Stitches per 10 cm linear	20 +/- 1
Colour	Olive-green
UV stability	Meets DIN 53387 Standard
Colour fastness:	Xenon test: Bleu-scale >7 , Grey-scale > 4
Colour lining	White / Yellow / Red / Bleu
Roll width	200 / 400 cm +/- 2 cm
Roll length	Standard 25 mtrs
Applications	Multifunctional
Additional information	Before installation make sure the rolls are from the same production code (first five digits of the roll number) Project.
Version	1 > 23/02/2011